

New topography software for CAM

Peter Hjort Lauritzen[§], Julio Bacmeister[§], Mark Taylor^{*} and Rich Neale[§]



CESM AMWG meeting, February 1-3, 2012

§ NCAR *Sandia National Laboratories

(thanks to Andy Mai for doing all the runs and diagnostics)



Surface variables

- **PHIS**: surface geopotential
- SGH30: standard deviation of topography on scales approximately < 3 km. Used for turbulent mountain stress (TMS) parameterization (sub-grid-scale orographic drag)
- SGH: standard deviation of topography on scales approximately > 3km (and < grid scale) (momentum flux deposition due to unresolved gravity waves)
- LANDFRAC: land-ocean mask
- LANDM_COSLAT: "smoothed" LANDFRAC (not used in CAM5)

Default topo-data generation for regular lat-lon grids

- A. Bin USGS 30 arc seconds (~1 km) data to 10 arc minutes grid (~15 km)
- B. While doing A. compute SGH30 (code in /atm/cam/tools/definehires/ does A. and B.)
- C. Bin 10 arc minutes data to target lat-lon grid (compute SGH)
- D. Filter PHIS (dynamical core dependent)





"Default" topo-data generation for non lat-lon grids

Default software does not support non lat-lon grids so CAM-FV topo-variables at similar lat-lon resolution are linearly interpolated to target grid (and smoothed further)



Issues with "default" procedure

- Computing SGH and SGH30 on a lat-lon grid (as done currently) leads to *anisotropic* separation of scales
- SGH is not recomputed to include the extra sub-grid-scale variance in the sub-grid-scale due to interpolation and explicit smoothing/filtering of PHIS
- Interpolation of PHIS is not volume conserving (conservative remapping may introduce desirable/consistent "smoothing")

Default topo-data generation for regr

to ta

A. b. 'SGS 30 arc seconds (~1 kn
B. Whn A. compute SGH3 (code in /atn is seconds A. and B.)

Bin 10 ar

D. Filter PHIS

С.

ta to 10 arc mi

r lat-lon grids



Software to generate topo-data has been completely rewritten to directly accommodate unstructured grids and enforce more physical consistency

(as



otropic

- Computing SGH and separation of scales
- SGH is not recomputed to include due to interpolation and explicit s
- Interpolation of PHIS is not volume desirable/consistent "smoothing")

tra sub-gric variance in the sub-grid-scale hing/filtering c HIS nserving (conservative remapping may introduce

ntly) lead.

New software (3 Fortran programs)

 GEN_NETCDF_FROM_USGS: Reads USGS 30 arc seconds terrain dataset in 33 tiles and converts it a single NetCDF file (7.5GB; elevation stored as integer)

(only changes to raw data is for the Caspian sea)



http://eros.usgs.gov/#/Find_Data/Products_and_Data_Available/gtopo30_info



New software (3 Fortran programs)

 2. BIN_TD_CUBE: bin USGS 30 arc seconds data to ~3km quasiisotropic cubed-sphere grid and compute SGH30
 Adjustments to land fraction: Extend land fraction for Ross Ice shelf by setting all landfractions south of 79S to 1



-> quasi-isotropic separation of scales (for SGH30 and SGH).

3. CUBE_TD_TARGET: Rigorously remap (volume conserving) variables from ~3km cubed-sphere to any structured or unstructured target grid (compute SGH) If PHIS is smoothed (externally or internally) SGH is re-computed to account for smoothing in sub-grid-scale variance



SGH30

Default software used

New software used



More isotropic filtering (different cut-off scale): -> significantly less "energy" in SGH30 with new topo software

SGH

Default software used

New software used



More isotropic filtering (different cut-off scale): -> significantly more "energy" in SGH with new topo software Exploratory simulations with CAM-FV and CAM-SE (at 1 degree resolutions) to assess the effect of "consistent" SGH and SGH30

• Will primarily show results for CAM-FV, however, the CAM-SE simulations show similar changes to the climate for this experiment setup

Runs (10 year):

- Control: default topo files
- Consistent: PHIS from control but consistent SGH and SGH30 computed using new software

Sea level pressure (PSL): CAM-FV 1 degree

Control and OBS





Sea level pressure (PSL): CAM-FV 1 degree





Control and OBS







Control and OBS



Control

f.e11.F2000C5.f09_f09.001

Near surface wind



MIN = 0.20 MAX = 17.16

Winds too weak along coast of Antarctica in control run -> Winds improve significantly with new SGH and SGH30! In particular note the improvements near the Ross Ice shelf and Transantarctic Mountains

 f.e11.F2000C5.f09_f09.001 - NCEP

 Near surface wind
 m/s

 Image: marked black bla



Control

m/s

9 f09.001

Surface wind stress: CAM-FV 1 degree

Control and OBS





Surface wind stress: CAM-FV 1 degree



Zonal temperature: CAM-FV 1 degree

DJF f.e11.F2000C5.f09_f09.001 (yrs 1-10) NCEP Temperature Temperature κ 70 -Height (km) Pressure (mb) Pressure (mb) 300 1000 90N 60N 30N 30S 60S 90S 60N 30N 30S 60S MIN = 188.72 MAX = 298.92 MIN = 194.76 MAX = 299.49 210 230 f.e11.F2000C5.f09 f09.001 - NCEP Temperature K MIN = -14.57 MAX = 6.86 Pressure (mb) Height (km) -5 -7 -9 30S 60S 60N 30N

Control and OBS



Smoothing PHIS for CAM-SE (and MPAS)

Ongoing project to internally smooth topography in new software:

- remove 2*dx oscillations, force PHIS near coast lines to be zero over ocean, etc. all while preserving PHIS volume
- being done using finite-volume transport scheme technology

How and how much to smooth PHIS is a somewhat "grey area" of climate modeling ... but it matters ... see next slide

Precipitation Rate (CAM-SE)











Transport and related ongoing developments in CAM

AMWG, February 1-3

Peter Hjort Lauritzen[§], Christoph Erath^{§,†},

Trey White[§], Julio Bacmeister[§], and Mark Taylor^{*}

[§]NCAR ^{*}Sandia National Laboratories

[†]University of Colorado, Boulder





NCAR Earth System Laboratory

CSLaM scheme (Conservative Semi-Lagrangian Multi-tracer) is being integrated into CAM-SE; major software engineering effort (Erath, Taylor) (e.g., communication infrastructure did not support stencils beyond shared points on element boundaries)



- 2D version running; next: couple to spectral element dynamics



Figure courtesy of C.Erath

CSLaM scheme (Conservative Semi-Lagrangian Multi-tracer) is being integrated into CAM-SE; major software engineering effort (communication infrastructure did not support stencils beyond shared points on element boundaries)

Adding specified dynamics capability in CAM-SE (PI: J.-F. Lamarque)

Separate physics and dynamics grids in CAM-SE (PI: J. Bacmeister)

New idealized standard test case suite for transport (Lauritzen et al., 2012, GMDD)

Results from large ensemble of state of the art transport schemes (Lauritzen et. al., 2012, in prep)

Summer school on global non-hydrostatic dynamical cores at NCAR (Organizers: C. Jablonowski, P.H. Lauritzen, M.A.Taylor, R.D.Nair, P.A.Ullrich)



Dynamical Core Model Intercomparison Project (DCMIP)

July 30th, 2012 - August 10th, 2012 National Center for Atmospheric Research, Boulder, Colorado

Application Deadline: March 15th, 2012